Ultrasonic point welder 'QUPPA'

Easy to pack, easy to open / Maintains product appeal with inconspicuous spot-weld / For food safety measures

-What is an Ultrasonic point welder?

You can easily weld plastic packaging at a point like a stapler, but with no staples. Insert the sealing surface between the teeth and press. The hand piece generates ultrasonic waves and spot-welds by heat in two seconds or less.

-Very easy to use

Press the hand piece





▼Hand piece generates 57,000 oscillations per second.

-Ideal for food safety measures

You are able to prevent unwanted materials such as staples, rubber bands, etc., from entering packages sealed by QUPPA.



-Easy to pack, easy to open.

Easily and efficiently seals by inserting packaging in the handset and lightly pressing it together. Packages open easily without the nuisance of tape.


-Presents packaged goods in an attractive way.

Nade in JAPAN

Films, wrap, staples, rubber bands and cellophane tapes disrupt product appeal. But using QUPPA helps to maintain that appeal with small inconspicuous spot-welds.










Added level of safety

QUPPA can be used to create a type of tamper proof seal easily at low cost, and can also seal any plastic containers that you may already have.

With QUPPA, you can be more confident that your snap-on and clam shell packages will be securely and reliably sealed.

-You can easily see if the seal has been broken.

Safety



-Low operating cost QUPPA vs. Traditional food pack tapes -



- ▼ each sealed in 4 spots
 (4000seals)
 ⇒ 20 ¢
- ▼ Food pack tape


 (1pack = 10cm)
 (1roll = 500packs) x 2
 ⇒ \$ 5.60



Compatible sealing materials

*For upper side

*For lower side		PSP	OPS	PVC	HIPS	PPF	PP	A-PET
	PSP	0	0		0	×	×	0
	OPS	0	0	\triangle	0	0	0	0
	PVC	×	×		Δ	×	Δ	Δ
	HIPS	0	0	×	0	×	×	0
	PPF	×	×	×	×	0	0	×
	PP	×	×	×	×	0	0	×
	A-PET	×	×	Δ	0	0	0	0



Point 1 / Work efficiency

- Easy to see contact points



Point 2 / Work efficiency

- Magnetized hand piece Internal magnet holds the hand piece easily Light weight hand piece; 200g

Point 3 / Safety

- No risk of being burned It does not work when you have your finger pinched.



Point 4 / Safety

- Does not work when teeth contact directly.

Point 5 / Safety

- No need for a transformer Power cord length :3.2m

Point 6 / Safety

- High durability and easy maintenance Moving parts are enclosed in the hand piece body preventing them from coming loose or falling out.



Specifications

Specifications

Frequency	57kHz		
Output	20W		
Power Consumption	40VA		
Power Source	100-240V AC50/60Hz		
Dimensions / Main unit	W179*D183*H66 mm		
Dimensions / Hand piece	W36*D125*H54 mm		
Weight / Main unit	1000g		
Weight / Hand piece	200g		
Power cord	Coiled cord		
	Output Power Consumption Power Source Dimensions / Main unit Dimensions / Hand piece Weight / Main unit Weight / Hand piece		

ASAHI INDUSTRY PRODUCE



This form is the result that is pursued usability. It is equipped empty operation prevention system.

It is evolved easily and soundly. It is not only for food business, but also....

You can see infinity possibility in ultrasonic mini welder.





ASAHI INDUSTRY PRODUCE











1. Ergonomics Designed Grip

on the main unit with magnets and holder.

2. The hand piece is able to be fixed 3. Not slip easily with a high coefficient 4. The jack guard against dust. of friction rubber.

5. AC adapter is for 100V - 240V.

It is a design improved based on the opinion of the user. "QUPPA"

DISTINCTIVE FEATURES	Efficiency The design is easy to see a sealing point. As the hand piece is deep, you can use in a wide range.	Economy No expendables. Reasonable price and little electrical power.	SPECIFICATION Type Frequency Output Consumption Electric Power Power Source Dimensions(m/m) Weight	QP-01 57kHz 20W 40VA 100V~240V AC 50/60Hz Main Unit W179 × D183 × H66 Hand Piece W36 × D125 × H54 Main Unit Approx. 1kg Hand Piece Approx. 200g
Safety No worry to get burned.	Usage It's light and easy to use. We can use like a stapler.	Environment It can prevent alien mixture, and there are no wastes.	Power cord AC Adapter Input Output External dimension (m/m) Weight Approx. Cable Length * Due to our policy on ongoin	50cm (Spiral cord) 100V~240V AC 50/60Hz DC 15V 3.3A W62 × D97× H33 350g AC side 1,8m / DC side 1.5m ng product improvement, the

the specifications and external appearance are subject to change without notice.

ASAHI INDUSTRY CO., LTD.

3-3-1, Ichiban, Atsuta, Nagoya, City, Aichi, JAPAN 456-0053 TEL: 81-52-671-5191 FAX: 81-52-671-5196 E-mail : aspal@asahi-sg.co.jp Home page : http://www.asahi-sg.co.jp/

